

Burghart Olfactometer

<https://search.labfacilities.wur.nl/SearchDetail.aspx?deviceid=a6f4abd5-e484-4f00-8666-aeca14957f6c>

Brand

Burghart Messtechnik

Type

OL023 MD (variant OM8b+CC)



Contact

Paul Smeets (paul.smeets@wur.nl)

Edda Neuteboom (edda.neuteboom@wur.nl)

Sanne Boesveldt (sanne.boesveldt@wur.nl)

Organisation

Agrotechnology and Food Sciences

Department

Human Nutrition & Health

Description

A 8-channel olfactometer for accurate and controlled administration of odours to participant. This instrument can be used in combination with our 3T MRI for functional MRI studies. Principle

An olfactometer is a machine designed to deliver odours in a precisely-controlled manner, for instance in order to objectively assess olfactory function ('ability to smell') in a participant. This olfactometer provides a constant flow of air via a small tube to the nose of the participant. The air flow is heated to body temperature and humidified to > 60% relative humidity to prevent any thermal irritation and ensure that the nasal mucosa does not dry out.

The Burghart olfactometer works according to the Kobal switching principle. In this switching principle – schematically depicted below -, all flows are conveyed to the switching device: control (non-odorous air), dilution (non-odorous air) and odorant (odorous air).

During the inter-stimulus interval, the mixture of odorant and dilution is removed by means of a vacuum flow, and only the control flow reaches the participant's nose.

During stimulation, it is the control flow that is removed by means of a vacuum flow, and the mixture of odorant and dilution air flows into the participant's nose.

Technical Details

- Up to eight odorants in liquid or gaseous form
- Integrated pressure and vacuum supply
- Bi-rhinal mode possible
- Computer-controlled air flows
- Reproducible pain stimuli by using CO₂
- Water-heated system for stability of temperature
- Certified as a class IIa medical device according to 93/42/EC.

Applications

Burghart olfactometers are suitable to use for behavioural odour studies, electroencephalography (EEG) and functional MRI.

This olfactometer allows for application of rectangular-shaped chemical stimuli, which are necessary for the recording of event-related potentials (ERP) by means of EEG (electroencephalography). There are no magnetic valves and magnetic materials in the head of the olfactometer which could influence EEG recordings or fMRI testing.

Complementary Techniques

This instrument is complementary to the 3T MRI.